
Mossberg 9200 Disassembly

*Mossberg 9200
Disassembly*

*Downloaded from
cardprinter.sendafriend.co
by Cortez & Riddle*

INTRODUCTION TO THE MOSSBERG 9200 DISASSEMBLY PROCESS

The Mossberg 9200 is a classic semi-automatic shotgun that gained popularity for its reliability, smooth cycling, and affordability. Whether you are a seasoned shooter or a new owner, knowing how to perform a proper **Mossberg 9200 disassembly** is essential for routine cleaning,

maintenance, and troubleshooting. Over time, carbon buildup, dirt, and old lubricant can affect the shotgun's performance. Regular disassembly allows you to inspect wear parts, remove fouling, and keep the action running smoothly. This guide walks you through the entire process step by step, focusing on safety, technique, and best practices.

Before diving into the steps, it is important to understand that the Mossberg 9200 uses a unique gas-piston system that differs from many other shotguns. While the basic field strip is

straightforward, some parts require careful handling. This article covers everything from safety checks to reassembly tips, ensuring you can confidently tackle the task. Always refer to your owner's manual for model-specific details, as variations exist between early and later production runs.

WHY DISASSEMBLE THE MOSSBERG 9200?

Disassembling your shotgun is not just about cleaning; it is about prolonging the lifespan of the firearm. The Mossberg 9200 disassembly process helps you:

- Remove carbon deposits from the gas piston and cylinder
- Lubricate moving parts for consistent cycling

- Inspect for worn or damaged components like o-rings, springs, and extractors
- Clear obstructions that may cause failure to feed or eject
- Perform deep cleaning after heavy use, such as waterfowl hunting or competition

Neglecting disassembly can lead to malfunctions and accelerated wear. By mastering this skill, you become a more responsible gun owner and save money on professional gunsmith services.

SAFETY FIRST: ESSENTIAL PRECAUTIONS

Before you begin any **Mossberg 9200 disassembly**, safety must be your top priority. Follow these rules without

exception:

1. **Unload the shotgun completely.** Remove the magazine tube and visually and physically check the chamber and magazine. There should be no shells in the action or magazine.
2. **Wear eye protection.** Springs and small parts can fly out unexpectedly.
3. **Work in a well-lit, clean area.** Use a dedicated gun cleaning mat to prevent losing small components.
4. **Point the muzzle in a safe direction** at all times, even when disassembled.
5. **Keep a parts tray or container** to organize screws, pins, and

springs as you remove them.

Once you are confident the firearm is safe, you can proceed. If you are uncertain about any step, consult a qualified gunsmith or watch detailed video tutorials.

TOOLS AND WORKSTATION SETUP

For a complete Mossberg 9200 disassembly, you will need a few basic tools:

- Flathead screwdriver (small to medium)
- Phillips head screwdriver (size #1 or #2)
- Punch set (1/8" and 3/16" recommended)
- Small hammer or mallet (nylon or

- brass)
- Needlenose pliers
- Gun cleaning solvent and lubricant
- Clean rags or patches
- Magnetic parts tray (optional but helpful)

Lay out your tools in a logical order. Having a schematic diagram of the 9200 nearby can also be beneficial, especially if you are performing a disassembly for the first time.

STEP-BY-STEP MOSSBERG 9200 DISASSEMBLY GUIDE

Step 1:

Removing the Barrel and Forend

The first major step in **Mossberg 9200 disassembly** is to separate the barrel and forend from the receiver. Follow these steps:

1. Ensure the shotgun is unloaded and the bolt is closed.
2. Unscrew the magazine cap located at the front of the forend. Turn it counterclockwise until it comes off. Set the cap aside.
3. Slide the forend assembly forward toward the muzzle. It should slide

off the magazine tube. If it is tight, wiggle it gently while pulling.

4. Pull the barrel straight out of the receiver. Some models may require you to lift the barrel slightly to disengage it from the receiver ring.
5. Lay the barrel and forend on a clean surface.

At this point, you have already completed the basic field strip needed for cleaning the bore and the forend. However, for a deeper clean, continue disassembling the trigger group and bolt assembly.

Step 2: Removing the Trigger Group

The trigger group houses the firing mechanism and is removed as a single unit. This is a critical part of the **Mossberg 9200 disassembly** process.

1. Locate the two trigger group retaining pins on the receiver. One is just above the trigger guard; the other is near the back of the trigger housing.
2. Using a punch, gently tap the pins out from left to right. Some pins have a notch; note their

orientation.

3. Once both pins are removed, carefully pull the trigger group downward and out of the receiver. It may require a slight wiggle.
4. Place the trigger group aside. Be careful not to depress the trigger or move the hammer unnecessarily.

Now the receiver is largely empty, giving you access to the bolt carrier and action spring assembly.

Step 3: Removing the

Bolt and Carrier

The bolt assembly in the Mossberg 9200 includes the bolt head, carrier, and action bars. Here is how to extract them:

1. Pull the bolt carrier rearward until it stops. You will see the action spring guide rod protruding from the rear of the receiver.
2. Compress the action spring slightly and lift the spring guide rod out of its retaining notch. Slide the entire assembly out through the rear of the receiver.
3. Once the bolt carrier is free, separate the bolt from the carrier by rotating the bolt head and pulling it forward. Note the orientation of the firing pin and

extractor.

4. If needed, remove the action bars from the carrier by drifting out the small retaining pin.

At this stage, you have access to nearly all internal components for deep cleaning. The gas system remains attached to the barrel, which we address next.

Step 4: Disassembling the Gas System

The Mossberg 9200 uses a unique self-compensating gas system. Disassembling it is straightforward but

requires caution.

1. With the barrel removed, locate the gas piston and cylinder on the magazine tube extension.
2. Slide the forend sleeve forward to expose the piston. In most models, a spring-loaded detent holds the piston in place.
3. Using a punch or small screwdriver, depress the detent and slide the piston off the magazine tube.
4. Remove the piston ring(s) for cleaning. They may be stuck due to carbon buildup; soak them in solvent if needed.
5. Clean the gas ports in the barrel using a pipe cleaner or small brush.

Be careful not to lose the small detent spring. This part of the **Mossberg 9200 disassembly** is crucial for maintaining proper gas function.

Step 5: Detailed Disassembly of the Trigger Group (Optional)

Deep cleaning or replacing trigger parts requires further disassembly. Only proceed if you are confident; otherwise, leave the trigger group intact. For the complete **Mossberg 9200 disassembly** of the trigger housing:

1. Remove the hammer and spring by compressing the hammer strut and sliding the hammer pin out.
2. Drift out the trigger pin and sear pin. Note the positions of the trigger return spring and disconnecter.
3. Keep all parts organized. It is highly recommended to photograph the internals before removing anything.

Reassembly of the trigger group can be tricky due to spring tension. If you are not experienced, limit trigger disassembly to cleaning the exterior and flushing with solvent.

COMMON ISSUES DURING

MOSSBERG 9200 DISASSEMBLY

Even with careful steps, you may encounter problems. Here are frequent challenges and how to handle them:

- **Stuck forend:** If the forend will not slide off, apply penetrating oil around the magazine tube and let it sit for a few minutes. Avoid using excessive force which could damage the action bars.
- **Trigger group pins are tight:** Use a correctly sized punch and tap firmly with a nylon hammer. Sometimes a slight rust or burr can cause resistance. Clean the pin holes before reassembly.
- **Gas piston o-ring damaged:** Inspect the o-ring each time you disassemble. Replace it if cracked

find it is a common wear item.

- **Action spring guide rod not seating:** Ensure the spring is fully compressed when reinstalling. Lubricate the spring to prevent binding.

Patience is key. Rushing a disassembly can lead to lost parts or damage to the receiver.

REASSEMBLY TIPS

Reassembly is essentially the reverse of disassembly, but here are specific pointers for a smooth process:

1. Apply a thin layer of lubricant to the gas piston, action bars, and bolt carrier. Do not overlubricate - it attracts dirt.

2. When reinstalling the trigger group, ensure the safety selector is in the “fire” position to ease alignment.
3. Make sure the action spring guide rod is properly captured in its notch before closing the receiver.
4. After reassembly, function test the shotgun by manually cycling the action and checking the safety. Do not load ammunition until you are certain everything is correct.

A well-executed **Mossberg 9200 disassembly** followed by proper reassembly will restore your shotgun to reliable operation.

CONCLUSION

Mastering the **Mossberg 9200 disassembly** is an empowering skill that enhances your shooting experience and extends the life of your firearm. By following this comprehensive guide, you can safely and effectively break down the shotgun to its major components, clean every nook, and inspect for wear. Remember to always prioritize safety, work methodically, and refer to your owner’s manual for any model-specific nuances. With practice, the entire disassembly and reassembly process will become second nature. Your Mossberg 9200 will reward you with years of faithful service when cared for properly.